

CRAD-800 Suggested Product Specification

Part 2 - Products

2.01 Manufacturer

- A. Acceptable Manufacturer: Protek Systems, Incorporated, 1250 Wallace Dr. Unit B, Delray Beach, FL 33444; Telephone: 800-598-2153, Fax: 561-395-4771, www.proteksystem.com
- B. Substitutions: Not permitted.
- C. Provide all crash rail and wall protection from a single source.

2.02 Aluminum Diamond Plate Crash Rails

- A. CRAD-800 Aluminum Diamond Plate Crash Rail by Protek Systems, Inc.
 - 1. Material: 1/8-inch grade 3003 bright finish aluminum diamond plate
 - 2. Profile: 1 1/2-inch depth x 8-inch height with center V-groove
 - 3. Finish: Bright/Reflective finish
 - 4. Installation: Supplied in standard lengths and cut to fit in field by installers
 - 5. Custom lengths and profiles available. Other stainless steel grades and finishes also available.

2.03 Components

- A. ECAD-800 Aluminum Diamond Plate End Plates
 - 1. Material: 1/8-inch grade 3003 bright finish aluminum diamond plate
 - 2. Size: 1 9/16-inch x 8 1/8-inch
 - 3. Installation: Attaches to end plate brackets with fasteners through pre-drilled countersunk holes
- B. CRBAE-800 End Plate Bracket
 - 1. Material: .063-inch grade 3003 mill finish aluminum
 - 2. Secures CRAD-800 cover to wall
 - 3. To be used at crash rail end points. Wings allow for end plate attachment.
- C. CRBA-800 Standard Bracket
 - 1. Material: .063-inch grade 3003 mill finish aluminum
 - 2. Secures CRAD-800 cover to wall
 - 3. Spaced evenly not to exceed 32-inches on center
- D. SPLA-800 Splice Bracket
 - 1. Material: .063-inch grade 3003 mill finish aluminum
 - 2. Secures CRAD-800 cover to wall
 - 3. To be used as a splice where CRAD-800 covers meet

CRAD-800 Suggested Product Specification

- E. Attachment Options
 - 1. Fasteners: Pre-drilled holes available. Fasteners by others.