

REV A-3 21 2016

# **CRSC-800 Suggested Product Specification**

### Part 2 - Products

### 2.01 Manufacturer

- A. Acceptable Manufacturer: Protek Systems, Incorporated, 1250 Wallace Dr. Unit B, Delray Beach, FL 33444; Telephone: 800-598-2153, Fax: 561-395-4771, www.proteksystem.com
- B. Substitutions: Not permitted.
- C. Provide all crash rail and wall protection from a single source.

#### 2.02 Colored Stainless Steel Crash Rails

- A. CRSC-800 Colored Stainless Steel Crash Rail by Protek Systems, Inc.
  - 1. Material: Type 304 #4 satin finish colored stainless steel cover and mounting brackets
  - 2. Gauge: As recommended by manufacturer
  - 3. Profile: 1 1/2-inch depth x 8-inch height with center V-groove
  - 4. Manufacturer's standard colors. Custom colors available
  - 5. Finish: #4 satin finish
  - 6. Installation: Custom-fabricated per field measurements
  - 7. Custom lengths and profiles available. Other stainless steel grades and finishes available.

#### 2.03 Components

- A. ECSC-800 Colored Stainless Steel End Plates
  - 1. Material: 11ga type 304 #4 satin finish colored stainless steel
  - 2. Size: 1 9/16-inch x 8 1/8-inch
  - 3. Installation: Attaches to end plate brackets with fasteners through pre-drilled countersunk holes
- B. CRBSE-800 End Plate Bracket
  - 1. Material: 16ga type 304 #4 satin finish stainless steel
  - 2. Secures CRSC-800 cover to wall
  - 3. To be used at crash rail end points. Wings allow for end plate attachment.
- C. CRBS-800 Standard Bracket
  - 1. Material: 16ga type 304 #4 satin finish stainless steel
  - 2. Secures CRSC-800 cover to wall
  - 3. Spaced evenly not to exceed 32-inches on center



REV.A-3.21.2016

## **CRSC-800 Suggested Product Specification**

- D. SPL-800 Splice Bracket
  - 1. Material: 16ga type 304 #4 satin finish stainless steel
  - 2. Secures CRSC-800 cover to wall
  - 3. To be used as a splice where CRSC-800 covers meet

#### E. Attachment Options

1. Fasteners: Pre-drilled holes available. Fasteners by others.