REV.A-3.21.2016

CRS-200W Suggested Product Specification

Part 2 - Products

2.01 Manufacturer

- A. Acceptable Manufacturer: Protek Systems, Incorporated, 1250 Wallace Dr. Unit B, Delray Beach, FL 33444; Telephone: 800-598-2153, Fax: 561-395-4771, www.proteksystem.com
- B. Substitutions: Not permitted.
- C. Provide all crash rail and wall protection from a single source.

2.02 Welded Stainless Steel Crash Rails

- A. CRS-200W Welded Stainless Steel Crash Rail by Protek Systems, Inc.
 - 1. Material: 16ga type 304 #4 satin finish stainless steel cover and mounting brackets
 - 2. Profile: 1 1/2-inch depth x 5 1/2-inch height with center V-groove
 - 3. Finish: #4 satin finish
 - 4. Installation: Supplied in custom lengths with seamless welded ends
 - 5. Custom sizes and profiles available. Other stainless steel grades and finishes also available.

2.03 Components

- A. CRBS-200 Standard Bracket
 - 1. Material: 16ga type 304 #4 satin finish stainless steel
 - 2. Secures CRS-200W cover to wall
 - 3. Spaced evenly not to exceed 32-inches on center
- B. SPL-200 Splice Bracket
 - 1. Material: 16ga type 304 #4 satin finish stainless steel
 - 2. Secures CRS-200W cover to wall
 - 3. To be used as a splice where CRS-200W covers meet
- C. Attachment Options
 - 1. Fasteners: Pre-drilled holes available. Fasteners by others.